## NSN 5945-01-303-6062

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-303-6062

### **Overall Length:**

1.708 inches

### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.412 inches single mounting facility and 1.462 inches single mounting facility

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.990 inches single mounting facility and 1.010 inches single mounting facility

### **Overall Height:**

1.010 inches

#### **Overall Width:**

Between 1.400 inches and 1.420 inches

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.140 inches single mounting facility and 0.160 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

### **End Application:**

Hatch control

### **Winding Quantity:**

### **Purpose For Which Designed:**

General

### **Coil Quantity:**

### Winding Dc Resistance Rating:

210.0 ohms single winding

### **Duty Type:**

Continuous

#### **Arc Quenching Method:**

Air

### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

#### **Storage Type:**

General purpose warehouse

#### **Cubic Measure:**

2.450 cubic inches

### **Mounting Facility Pattern:**

Rectangular single mounting facility

### **Nonpile-up Main Contact Arrangement:**

6 pole, double throw, one position momentary

#### Time Delay:

0.015 seconds fixed operate and release time

# NSN 5945-01-303-6062

Electromagnetic Relay - Page 2 of 2



Op	erat	ing	٧	olta	ge	Ratin	g	An	d T	Гур	e A	At	Sp	ecif	icat	ioni	ifie	d 7	em	p:
	_																			

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:** 

200.0 ac and 28.0 dc

**Precious Material And Location:** 

Terminals gold

**Precious Material:** 

Gold

**Terminal Type And Quantity:** 

20 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300