NSN 5945-01-303-6062

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-303-6062

Overall Length:

1.708 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.412 inches single mounting facility and 1.462 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.990 inches single mounting facility and 1.010 inches single mounting facility

Overall Height:

1.010 inches

Overall Width:

Between 1.400 inches and 1.420 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.140 inches single mounting facility and 0.160 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

Hatch control

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

210.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

2.450 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

Time Delay:

0.015 seconds fixed operate and release time

NSN 5945-01-303-6062

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 200.0 ac and 28.0 dc Precious Material And Location: Terminals gold Precious Material:

Gold

Terminal Type And Quantity:

20 pin all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300