## NSN 5945-01-303-8036

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-303-8036

Overall Length:
100.0 millimeters
Center To Center Distance Between Mounting Facilities Parallel To Width:
35.0 millimeters single mounting facility
Overall Height:
92.0 millimeters
Overall Width:
45.0 millimeters
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
4.8 millimeters single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Height:
60.0 millimeters single mounting facility
Fragility Factor:
Moderately rugged
End Application:
Switchboard
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
414.0 cubic centimeters
Mounting Facility Pattern:
Diagonal single mounting facility
Nonpile-up Main Contact Arrangement:
6 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action
Operating Voltage Rating And Type At Specificationified Temp:

264.0 volts ac 25 degrees celsius single winding

## NSN 5945-01-303-8036

Electromagnetic Relay - Page 2 of 2



Main	Contact	Load	Current	Rating	At	Maximum	Rated	Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

220.0 ac

**Terminal Type And Quantity:** 

18 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300