NSN 5945-01-304-1899

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-304-1899

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.015 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.625 inches single mounting facility
Overall Height:
1.500 inches
Overall Width:
0.515 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
Pd panel encl
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.784 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility

Mounting Facility Pattern: In-line single mounting facility

NSN 5945-01-304-1899

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

24.0 milliamperes ac single winding

Time Delay:

0.05 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Energizing Element Power Rating:

4.0 watts

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300