

View Online at <https://aerobasegroup.com/nsn/5945-01-304-2230>

Overall Length:

1.181 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.995 inches second mounting facility and 1.005 inches second mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.120 inches second mounting facility and 0.130 inches second mounting facility

Overall Height:

0.875 inches

Overall Width:

0.398 inches

Unthreaded Mounting Hole Diameter:

0.091 inches second mounting facility and 0.101 inches second mounting facility

Fragility Factor:

Moderately rugged

End Application:

1520-01-125-5476 helicopter, obse

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

496.8 ohms single winding and 607.2 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole second mounting facility

Storage Type:

General purpose warehouse

Mounting Facility Pattern:

Rectangular second mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.005 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

29.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300