NSN 5945-01-305-0793

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-305-0793

| Thread Class: |
|--|
| 2b single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 1.688 inches |
| Overall Height: |
| 1.188 inches |
| Overall Width: |
| 1.906 inches |
| Case Material: |
| Plastic |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Silver |
| End Application: |
| Alarm, power f |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 475.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 8 threaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 3.822 cubic inches |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 note double throw one position momentary |

NSN 5945-01-305-0793

Electromagnetic Relay - Page 2 of 2



Operating Current Rating And Type: 51.0 milliamperes dc single winding **Operating Voltage Rating And Type At Specificationified Temp:** 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 120.0 ac **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 8 tab, solder lug all functions Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A03300