NSN 5945-01-305-2926

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-305-2926

Overall Length:

Between 0.778 inches and 0.798 inches

Overall Height:

Between 0.376 inches and 0.396 inches

Overall Width:

Between 0.380 inches and 0.400 inches

Fragility Factor:

Moderately rugged

End Application:

6740-01-193-2018 printer-processor, photographic film

Winding Quantity:

4

Purpose For Which Designed:

General

Coil Quantity:

4

Winding Dc Resistance Rating:

360.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.003 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

250.0 ac and 220.0 dc

Energizing Element Power Rating:

60.0 watts

Precious Material And Location:

Contacts silver and contact surfaces gold and contacts palladium

Precious Material:

Silver and gold and palladium

Terminal Type And Quantity:

8 pin all functions

NSN 5945-01-305-2926

Electromagnetic Relay - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300