## NSN 5945-01-306-1169

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-306-1169

| Overall Length:   |
|---|
| 0.770 inches  |
| Overall Height:   |
| 0.275 inches  |
| Overall Width:  |
| 0.265 inches  |
| Case Material:  |
| Plastic   |
| Fragility Factor:   |
| Moderately rugged   |
| End Application:  |
| Alcc/mse ate  |
| Winding Quantity:   |
| 1   |
| Purpose For Which Designed:                                   |
| General   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:                                 |
| 500.0 ohms single winding                                     |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:                          |
| 1 printed circuit terminal single mounting facility           |
| Storage Type:   |
| General purpose warehouse                                     |
| Features Provided:  |
| Coil voltage suppression and magnetic shield                  |
| Cubic Measure:  |
| 0.056 cubic inches  |
| Nonpile-up Main Contact Arrangement:                          |
| 1 pole, single throw, normally closed, momentary action       |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 5.0 volts dc 25 degrees celsius single winding                |
| Main Contact Load Current Rating At Maximum Rated Voltage:    |
| 250.0 milliamperes dc resistive load                          |
| Main Contact Maximum Voltage Rating In Volts:                 |
| 100.0 dc  |
| Energizing Element Power Rating:                              |
| 3.0 watts   |
| Terminal Type And Quantity:                                   |

1 printed circuit all functions

## NSN 5945-01-306-1169

Reed Relay - Page 2 of 2



| _ |    |    | - |       |   |
|---|----|----|---|-------|---|
| C | hο | 14 |   | .ife  |   |
| • |    |    | _ | .II C | - |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300