NSN 5945-01-306-4456

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-306-4456

Overall Laweths
Overall Length:
0.370 inches
Overall Height:
0.398 inches
Overall Width:
0.370 inches
Environmental Protection:
Hermetic and dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.054 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:
0.004 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Established reliability of 0.100
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:10 wire lead all functions

NSN 5945-01-306-4456

Electromagnetic Relay - Page 2 of 2



\r		•	C 2 t	ınn	11212	Į
OL.	, .		Cal	UII	Data	,

81349-mil-r-39016/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A03300