06-4458



roup.com/nsn/5945-01-306-4458

NSN 5945-01-306-4458 Electromagnetic Relay - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5
Overall Length:
0.335 inches
Overall Height:
0.280 inches
Overall Width:
0.335 inches
Environmental Protection:
Dustproof and corrosion resistant
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.031 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.004 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Established reliability of 0.100

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire lead all functions

NSN 5945-01-306-4458

Electromagnetic Relay - Page 2 of 2



Specification Data:

81349-mil-r-39016/18 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300