## NSN 5945-01-308-4035

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-308-4035

**Thread Class:** 2a second mounting facility **Overall Length:** 1.395 inches **Overall Height:** 1.187 inches Overall Width: 0.735 inches **Environmental Protection:** Vibration proof and shock proof and dustproof **Unthreaded Mounting Hole Diameter:** 0.091 inches first mounting facility **Fragility Factor:** Moderately rugged Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 30.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 unthreaded hole first mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 1.217 cubic inches **Thread Size:** 0.099 inches second mounting facility **Nonpile-up Main Contact Arrangement:** 6 pole, double throw, one position momentary Time Delay: 0.03 seconds fixed release time Operating Voltage Rating And Type At Specificationified Temp: 4.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load

**Precious Material And Location:** 

Contact arms and terminals silver and contact arms and terminals gold

## NSN 5945-01-308-4035

Electromagnetic Relay - Page 2 of 2



**Precious Material:** 

Silver and gold

**Thread Series Designator:** 

Unc second mounting facility

**Terminal Type And Quantity:** 

22 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300