NSN 5945-01-308-9262

Reed Relay - Page 1 of 1

Fragility Factor:



View Online at https://aerobasegroup.com/nsn/5945-01-308-9262

| Moderately rugged |
|---|
| End Application: |
| 6625-01-016-5966 gain phase meter; spruance class dd, los angeles class ssn (688), kidd class ddg, virginia class cgn (41), seawolf |
| class ssn, ticonderoga class cg (47), general purpose electronic test equipment gpete |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 966.0 ohms single winding |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Criticality Code Justification: |
| Feat |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 12.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 500.0 milliamperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 117.0 ac |
| Special Features: |
| Weapon system essential |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A03300 |
| |
| |