

View Online at <https://aerobasegroup.com/nsn/5945-01-308-9263>

**Overall Length:**

1.010 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.180 inches single mounting facility and 1.220 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.380 inches single mounting facility and 0.420 inches single mounting facility

**Overall Height:**

0.660 inches

**Overall Width:**

0.810 inches

**Environmental Protection:**

Dustproof and vibration proof and shock resistant

**Unthreaded Mounting Hole Diameter:**

0.076 inches single mounting facility and 0.116 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**End Application:**

An/mlq-t4

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

75.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Cubic Measure:**

0.540 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Time Delay:**

0.006 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

5.2 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Terminal Type And Quantity:**

14 wire hook all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300