

View Online at <https://aerobasegroup.com/nsn/5945-01-308-9263>

Overall Length:

1.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.180 inches single mounting facility and 1.220 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.380 inches single mounting facility and 0.420 inches single mounting facility

Overall Height:

0.660 inches

Overall Width:

0.810 inches

Environmental Protection:

Dustproof and vibration proof and shock resistant

Unthreaded Mounting Hole Diameter:

0.076 inches single mounting facility and 0.116 inches single mounting facility

Fragility Factor:

Moderately rugged

End Application:

An/mlq-t4

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

75.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Cubic Measure:

0.540 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.006 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

5.2 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300