NSN 5945-01-310-1317

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-310-1317

Overall	Length:
---------	---------

0.810 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility and 1.078 inches single mounting facility

Overall Height:

0.640 inches

Overall Width:

0.312 inches

Mounting Slot Width:

0.133 inches single mounting facility

Environmental Protection:

Dustproof and vibration resistant and shock resistant

Fragility Factor:

Moderately rugged

End Application:

Slam handling

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

23.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.162 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.004 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac motor load and 1.0 amperes dc motor load

NSN 5945-01-310-1317

Electromagnetic Relay - Page 2 of 2



	~			D 41		
wain	Contact	Maximum	voitage	Rating	ı ın	voits:

115.0 ac and 28.0 dc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300