NSN 5945-01-310-9638

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-310-9638

| View Online at https://aerobasegroup.com/nsn/5945-01-310-9638 |
|---|
| Overall Length: |
| 4.440 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.865 inches single mounting facility and 3.885 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.740 inches single mounting facility and 2.760 inches single mounting facility |
| Overall Height: |
| 3.550 inches |
| Overall Width: |
| 3.310 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.213 inches single mounting facility and 0.228 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Silver |
| End Application: |
| E-3 facs raov |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 46.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Otaniana Tanan |

Storage Type:

General purpose warehouse

Cubic Measure:

52.172 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.04 seconds fixed release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

NSN 5945-01-310-9638

Electromagnetic Relay - Page 2 of 2

A03300



| Auxiliary Contact Maximum Voltage Rating In Volts: |
|---|
| 28.0 dc |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 100.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 200.0 ac |
| Auxiliary Contact Load Current Rating At Maximum Rated Voltage: |
| 5.0 probe dc resistive load |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Terminal Type And Quantity: |
| 6 threaded stud all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |