NSN 5945-01-310-9638

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-310-9638

View Online at https://aerobasegroup.com/nsn/5945-01-310-9638
Overall Length:
4.440 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.865 inches single mounting facility and 3.885 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.740 inches single mounting facility and 2.760 inches single mounting facility
Overall Height:
3.550 inches
Overall Width:
3.310 inches
Unthreaded Mounting Hole Diameter:
0.213 inches single mounting facility and 0.228 inches single mounting facility
Fragility Factor:
Moderately rugged
Contact Material:
Silver
End Application:
E-3 facs raov
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
46.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Otaniana Tanan

Storage Type:

General purpose warehouse

Cubic Measure:

52.172 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.04 seconds fixed release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

NSN 5945-01-310-9638

Electromagnetic Relay - Page 2 of 2

A03300



Auxiliary Contact Maximum Voltage Rating In Volts:
28.0 dc
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 amperes ac resistive load
Main Contact Maximum Voltage Rating In Volts:
200.0 ac
Auxiliary Contact Load Current Rating At Maximum Rated Voltage:
5.0 probe dc resistive load
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Terminal Type And Quantity:
6 threaded stud all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: