## NSN 5945-01-313-3899

Electromagnetic Relay - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5945-01-313-3899

0.610 inches
Overall Height:
0.320 inches
Overall Width:
0.610 inches
Fragility Factor:
Moderately rugged
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Winding Dc Resistance Rating:
37.0 ohms all windings
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.119 cubic inches
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Operating Voltage Rating And Type At Specificationified Temp:
6.0 volts dc 25 degrees celsius all windings
Main Contact Load Current Rating At Maximum Rated Voltage:
125.0 milliamperes ac resistive load and 2.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Special Features:
Failure rate 1.0 percent per 10, 000 cycles
Test Data Document:
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
16 wire lead all functions

81349-mil-r-39016/35 government specification

**Specification Data:** 

## NSN 5945-01-313-3899

Electromagnetic Relay - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300