NSN 5945-01-313-8398

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-313-8398

Overall Length:

6.230 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.880 inches single mounting facility

Overall Height:

3.090 inches

Overall Width:

3.250 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.199 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Latching contacts

Cubic Measure:

62.564 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.05 seconds fixed operate and release time

NSN 5945-01-313-8398

Electromagnetic Relay - Page 2 of 2



Nonpile-up Auxiliary Contact Arrangement: 1 pole, double throw, one position momentary Auxiliary Contact Maximum Voltage Rating In Volts: 480.0 ac **Operating Voltage Rating And Type At Specificationified Temp:** 250.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 15.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 480.0 ac and 110.0 dc Auxiliary Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load **Terminal Type And Quantity:** 11 screw all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300