## NSN 5945-01-313-8398

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-313-8398

Overall Length:
6.230 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.750 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.880 inches single mounting facility
Overall Height:
3.090 inches
Overall Width:
3.250 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.199 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
6 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Latching contacts
Cubic Measure:
62.564 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:

0.05 seconds fixed operate and release time

## NSN 5945-01-313-8398

Electromagnetic Relay - Page 2 of 2



## **Nonpile-up Auxiliary Contact Arrangement:**

1 pole, double throw, one position momentary

**Auxiliary Contact Maximum Voltage Rating In Volts:** 

480.0 ac

**Operating Voltage Rating And Type At Specificationified Temp:** 

250.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:** 

10.0 amperes ac resistive load

**Terminal Type And Quantity:** 

11 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300