

View Online at <https://aerobasegroup.com/nsn/5945-01-315-1897>

**Fragility Factor:**

Moderately rugged

**Contact Material:**

Silver

**Contact Surface Treatment:**

Gold

**End Application:**

Second antenn

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

1 plug-in terminal single mounting facility

**Storage Type:**

General purpose warehouse

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Time Delay:**

0.20 seconds fixed operate time and 5.00 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

24.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes ac inductive load

**Main Contact Maximum Voltage Rating In Volts:**

240.0 ac and 100.0 dc

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Precious Material:**

Silver and gold

**Terminal Type And Quantity:**

1 standard tube base all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300