NSN 5945-01-315-1898

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-315-1898

Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
End Application:
Second antenn
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.20 seconds fixed release time and 5.00 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
1.0 amperes ac inductive load
Main Contact Maximum Voltage Rating In Volts:
240.0 ac and 100.0 dc
Precious Material And Location:
Contacts silver and contact surfaces gold
Precious Material:
Silver and gold
Terminal Type And Quantity:
1 standard tube base all functions
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5945-01-315-1898

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300