NSN 5945-01-315-7126

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-315-7126
Overall Length:
1.025 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Overall Height:
1.125 inches
Overall Width:
0.525 inches
Mounting Slot Width:
0.150 inches single mounting facility
Environmental Protection:
Shock proof and vibration resistant and hermetic
Fragility Factor:
Moderately rugged
End Application:
6625-01-237-4658 test set, antenna dr; missile, minuteman lgm-30; support equipment, b-52 aircraft
Frequency In Hertz:
60.0 or 400.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.605 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Criticality Code Justification:
Feat
Time Delay:

0.05 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

NSN 5945-01-315-7126

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load

Special Features:

Failure rate 0.3 percent per 10, 000 cycles; weapon system essential

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

96906-ms27401 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.