

View Online at <https://aerobasegroup.com/nsn/5945-01-316-2945>

Overall Length:

1.483 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.412 inches single mounting facility and 1.462 inches single mounting facility

Overall Height:

1.010 inches

Overall Width:

1.053 inches

Mounting Slot Width:

0.150 inches single mounting facility

Environmental Protection:

Shock resistant and vibration resistant and hermetic

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.577 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

Time Delay:

0.015 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

42.0 dc

Special Features:

Permanent magnet drive

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 wire hook all functions

Specification Data:

81349-mil-r-6106/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300