

View Online at <https://aerobasegroup.com/nsn/5945-01-316-2946>

Overall Length:

0.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.057 inches first mounting facility and 1.067 inches first mounting facility

Overall Height:

Between 0.850 inches and 0.900 inches

Overall Width:

0.400 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.115 inches first mounting facility and 0.130 inches first mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

2

Purpose For Which Designed:

General

Coil Quantity:

2

Winding Dc Resistance Rating:

975.0 ohms all windings

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole first mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Latching contacts and polarized

Cubic Measure:

0.288 cubic inches

Mounting Facility Pattern:

In-line first mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

150.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate 1.0 percent per 10, 000 cycles

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

10 pin all functions

Specification Data:

81349-mil-r-39016/32 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300