

View Online at <https://aerobasegroup.com/nsn/5945-01-316-2947>

Overall Length:

1.700 inches

Overall Diameter:

Between 1.100 inches and 1.130 inches

Environmental Protection:

Dustproof and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.131 inches single mounting facility and 0.151 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

290.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.704 cubic inches

Mounting Facility Pattern:

Circular single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Time Delay:

0.01 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

6.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

3600.0 dc

Test Data Document:

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 turret energizing element

Specification Data:

81349-mil-r-83725/7 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300