

View Online at <https://aerobasegroup.com/nsn/5945-01-316-8013>

Overall Length:

0.810 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches second mounting facility

Overall Height:

0.640 inches

Overall Width:

0.810 inches

Mounting Slot Width:

0.133 inches second mounting facility

Environmental Protection:

Shock resistant and vibration resistant

Fragility Factor:

Moderately rugged

End Application:

Harpoon almts

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

400.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 slotted hole second mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.420 cubic inches

Mounting Facility Pattern:

Triangle second mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.006 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.078 inches second mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Terminal Type And Quantity:

14 pin all functions

Specification Data:

55974-6411305 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300