

View Online at <https://aerobasegroup.com/nsn/5945-01-316-8013>

**Overall Length:**

0.810 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.500 inches second mounting facility

**Overall Height:**

0.640 inches

**Overall Width:**

0.810 inches

**Mounting Slot Width:**

0.133 inches second mounting facility

**Environmental Protection:**

Shock resistant and vibration resistant

**Fragility Factor:**

Moderately rugged

**End Application:**

Harpoon almts

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

400.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

3 slotted hole second mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

0.420 cubic inches

**Mounting Facility Pattern:**

Triangle second mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Time Delay:**

0.006 seconds fixed operate and release time

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.078 inches second mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes dc motor load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Terminal Type And Quantity:**

14 pin all functions

**Specification Data:**

55974-6411305 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300