# NSN 5945-01-317-0506

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-317-0506

## **Overall Length:**

2.500 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.990 inches single mounting facility and 2.010 inches single mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.052 inches single mounting facility and 1.072 inches single mounting facility

#### **Overall Height:**

2.400 inches

**Overall Width:** 

1.465 inches

Environmental Protection:

Dustproof and shock resistant and hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.173 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

# End Application:

Misc parts

Frequency In Hertz:

60.0 or 400.0

### Winding Quantity:

1

## **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

Duty Type:

Continuous

#### Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Cubic Measure:**

8.790 cubic inches

#### **Mounting Facility Pattern:**

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

#### Time Delay:

0.02 seconds fixed operate time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

# NSN 5945-01-317-0506

Electromagnetic Relay - Page 2 of 2



#### Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes dc motor load

#### Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

# Terminal Type And Quantity:

10 screw all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300