## NSN 5945-01-317-0509

Electromagnetic Relay - Page 1 of 2

2.0 amperes ac resistive load



View Online at https://aerobasegroup.com/nsn/5945-01-317-0509

| Overall Length:  |
|--|
| 6.380 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                                 |
| 5.875 inches single mounting facility  |
| Overall Height:  |
| 3.190 inches   |
| Overall Width:   |
| 6.380 inches   |
| Environmental Protection:  |
| Watertight   |
| Unthreaded Mounting Hole Diameter:   |
| 0.262 inches single mounting facility  |
| Fragility Factor:  |
| Moderately rugged  |
| Frequency In Hertz:  |
| 20000.0  |
| Winding Quantity:  |
| 1  |
| Purpose For Which Designed:  |
| General  |
| Coil Quantity:   |
| 1  |
| Duty Type:   |
| Continuous   |
| Arc Quenching Method:  |
| Air  |
| Mounting Facility Type And Quantity:   |
| 3 unthreaded hole single mounting facility   |
| Storage Type:  |
| General purpose warehouse  |
| Cubic Measure:   |
| 129.847 cubic inches   |
| Mounting Facility Pattern:   |
| Triangle single mounting facility  |
| Nonpile-up Main Contact Arrangement:   |
| 1 pole, double throw, one position momentary   |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 4.750 inches single mounting facility  |
| Operating Voltage Rating And Type At Specificationified Temp:  |
| 90.0 volts ac 25 degrees celsius single winding  |
| Main Contact Load Current Rating At Maximum Rated Voltage:   |

## NSN 5945-01-317-0509

Electromagnetic Relay - Page 2 of 2



| Main Contact Maximum Voltage Rating In Volts: |
|---|
| 115.0 ac                                      |
| Terminal Type And Quantity:                   |
| 5 pin all functions                           |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |
| Demilitarization:                             |
|   |

No

Fiig:

A03300