# NSN 5945-01-317-1836

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-317-1836

Overall Length:
1.718 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches single mounting facility
Overall Height:
1.810 inches
Overall Width:
Between 1.005 inches and 1.025 inches
Mounting Slot Width:
0.150 inches single mounting facility
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
End Application:
Misc parts
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
3.314 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Time Delay:
30.00 seconds fixed operate time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-317-1836

Electromagnetic Relay - Page 2 of 2



#### Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

### Terminal Type And Quantity:

16 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300