# NSN 5945-01-317-1845

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-317-1845

### Overall Length:

1.718 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.615 inches single mounting facility and 0.635 inches single mounting facility

#### **Overall Height:**

1.810 inches

#### **Overall Width:**

Between 1.005 inches and 1.025 inches

#### **Mounting Slot Width:**

0.150 inches single mounting facility

#### **Environmental Protection:**

Dustproof

#### Fragility Factor:

Moderately rugged

#### End Application:

Misc parts

#### Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

#### Storage Type:

General purpose warehouse

#### Cubic Measure:

1.545 cubic inches

#### **Mounting Facility Pattern:**

Triangle single mounting facility

#### Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

#### Time Delay:

3.00 seconds fixed operate time

#### Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches single mounting facility and 1.446 inches single mounting facility

#### Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-317-1845

Electromagnetic Relay - Page 2 of 2



#### Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

16 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300