NSN 5945-01-317-6175

Electromagnetic Relay - Page 1 of 2



Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.312 inches
Overall Diameter:
1.046 inches
Case Material:
Metal
Environmental Protection:
Hermetic and dustproof
Fragility Factor:
Moderately rugged
End Application:
Mk641 mod0 te
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
Winding Dc Resistance Rating: 60.0 ohms single winding
60.0 ohms single winding
60.0 ohms single winding Duty Type:
60.0 ohms single winding Duty Type: Continuous
60.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity:
60.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility
60.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type:
60.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse
60.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse Thready Qty Per Inch (tpi):
Outy Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 single mounting facility
60.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size:
Outy Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility
Outy Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern:
Outy Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: In-line single mounting facility
Duty Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement:
Duty Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary
Duty Type: Continuous Mounting Facility Type And Quantity: 2 threaded stud single mounting facility Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Time Delay:

12.0 volts dc 25 degrees celsius single winding

NSN 5945-01-317-6175

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300