

View Online at <https://aerobasegroup.com/nsn/5945-01-319-1654>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

Between 1.210 inches and 1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.873 inches single mounting facility and 0.877 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.623 inches single mounting facility and 0.627 inches single mounting facility

Overall Height:

Between 1.890 inches and 1.930 inches

Overall Width:

Between 0.960 inches and 1.000 inches

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

End Application:

An/slq-48, (uc

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.900 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

10 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300