

View Online at <https://aerobasegroup.com/nsn/5945-01-319-1654>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

Between 1.210 inches and 1.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.873 inches single mounting facility and 0.877 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.623 inches single mounting facility and 0.627 inches single mounting facility

**Overall Height:**

Between 1.890 inches and 1.930 inches

**Overall Width:**

Between 0.960 inches and 1.000 inches

**Environmental Protection:**

Dustproof

**Fragility Factor:**

Moderately rugged

**End Application:**

An/slq-48, (uc

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 threaded stud single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

1.900 cubic inches

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.112 inches single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

10 wire hook all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300