NSN 5945-01-319-3008

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-319-3008
Overall Length:
0.810 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.590 inches single mounting facility and 0.610 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.190 inches single mounting facility and 0.210 inches single mounting facility
Overall Height:
0.617 inches
Overall Width:
0.410 inches
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
End Application:
Mk85m0d6 x he
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
20.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.136 cubic inches

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.004 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

5.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

160.0 milliamperes dc lamp load

NSN 5945-01-319-3008

Electromagnetic Relay - Page 2 of 2



115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300