

View Online at <https://aerobasegroup.com/nsn/5945-01-320-4939>

Thread Class:

2b second mounting facility

Thread Direction:

Right-hand second mounting facility

Overall Length:

Between 4.312 inches and 4.374 inches

Overall Height:

Between 3.925 inches and 4.053 inches

Overall Width:

Between 1.719 inches and 1.781 inches

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold

End Application:

Navy equip

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

204.3 ohms single winding and 249.7 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 threaded stud first mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

31.573 cubic inches

Thready Qty Per Inch (tpi):

32 second mounting facility

Thread Size:

0.138 inches second mounting facility

Mounting Facility Pattern:

In-line first mounting facility

Nonpile-up Main Contact Arrangement:

16 pole, double throw, one position momentary

Time Delay:

25.00 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac

Special Features:

8 contacts are dry circuits with the following current ratings: 1 amp, 28.0 vdc resistive; 125 milliamps, 120.0 vac, 60 hz resistive

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc second mounting facility

Terminal Type And Quantity:

50 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300