

View Online at <https://aerobasegroup.com/nsn/5945-01-320-5737>

Overall Length:

Between 3.266 inches and 3.358 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.995 inches single mounting facility and 2.005 inches single mounting facility

Overall Height:

2.718 inches

Overall Width:

Between 2.625 inches and 2.655 inches

Mounting Slot Width:

0.088 inches single mounting facility and 0.098 inches single mounting facility

Environmental Protection:

Shock proof and vibration proof

Fragility Factor:

Moderately rugged

End Application:

Radio test se

Frequency In Hertz:

60.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

102.0 ohms single winding and 138.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

24.232 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

2.495 inches single mounting facility and 2.505 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

25.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

230.0 ac

Terminal Type And Quantity:

14 screw all functions

Specification Data:

95105-970-2303 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300