

View Online at <https://aerobasegroup.com/nsn/5945-01-320-5737>

**Overall Length:**

Between 3.266 inches and 3.358 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.995 inches single mounting facility and 2.005 inches single mounting facility

**Overall Height:**

2.718 inches

**Overall Width:**

Between 2.625 inches and 2.655 inches

**Mounting Slot Width:**

0.088 inches single mounting facility and 0.098 inches single mounting facility

**Environmental Protection:**

Shock proof and vibration proof

**Fragility Factor:**

Moderately rugged

**End Application:**

Radio test se

**Frequency In Hertz:**

60.0

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

102.0 ohms single winding and 138.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

24.232 cubic inches

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

2.495 inches single mounting facility and 2.505 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

25.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

230.0 ac

**Terminal Type And Quantity:**

14 screw all functions

**Specification Data:**

95105-970-2303 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300