NSN 5945-01-321-1883

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-321-1883

Overall Length:

1.770 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.401 inches single mounting facility and 1.441 inches single mounting facility

Overall Height:

Between 0.505 inches and 0.525 inches

Overall Width:

1.718 inches

Mounting Slot Width:

0.140 inches single mounting facility and 0.160 inches single mounting facility

Environmental Protection:

Hermetic and vibration proof and shock proof

Fragility Factor:

Moderately rugged

End Application:

Starter mtr

Frequency In Hertz:

Between 50.0 and 400.0

Winding Quantity:

•

Purpose For Which Designed:

General

Coil Quantity:

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.605 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Current Rating And Type:

24.0 milliamperes ac single winding

Time Delay:

0.05 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

NSN 5945-01-321-1883

Electromagnetic Relay - Page 2 of 2



	Main	Contact	Load Curi	rent Rating	At Ma	ximum	Rated '	Voltage:
--	------	---------	------------------	-------------	-------	-------	---------	----------

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Terminal Type And Quantity:

5 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300