# NSN 5945-01-321-9410

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-321-9410

# Overall Length:

1.718 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Overall Height:** 

1.455 inches

**Overall Width:** 

Between 0.505 inches and 0.525 inches

**Mounting Slot Width:** 

0.150 inches single mounting facility

**Environmental Protection:** 

Shock proof and vibration proof

**Fragility Factor:** 

Moderately rugged

Frequency In Hertz:

60.0

**Winding Quantity:** 

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

1

**Duty Type:** 

Continuous

**Arc Quenching Method:** 

Air

### **Mounting Facility Type And Quantity:**

2 slotted hole single mounting facility

Storage Type:

General purpose warehouse

**Cubic Measure:** 

1.312 cubic inches

#### **Mounting Facility Pattern:**

In-line single mounting facility

#### **Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

# **Operating Current Rating And Type:**

24.0 milliamperes ac single winding

Time Delay:

0.50 seconds fixed release time

#### Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

# NSN 5945-01-321-9410

Electromagnetic Relay - Page 2 of 2



# Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

9 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300