

View Online at <https://aerobasegroup.com/nsn/5945-01-322-7008>

Overall Length:

1.280 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.800 inches first mounting facility and 0.820 inches first mounting facility

Overall Height:

0.810 inches

Overall Width:

0.810 inches

Mounting Slot Width:

0.123 inches first mounting facility and 0.143 inches first mounting facility

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

End Application:

Mpcd

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

90.0 ohms single winding and 110.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 slotted hole first mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.840 cubic inches

Mounting Facility Pattern:

Triangle first mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

161.0 milliamperes dc single winding

Time Delay:

0.006 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.062 inches first mounting facility and 1.078 inches first mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate "m" is 1.0 percent per 10, 000 cycles.

Test Data Document:

81349-mil-r-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 pin all functions

Specification Data:

81349-mil-r-83536/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300