NSN 5945-01-323-1163

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-323-1163

Overall Length:

0.610 inches

Overall Height:

0.320 inches

Overall Width:

0.610 inches

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

End Application:

F15e cbil

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

648.0 ohms single winding and 792.0 ohms single winding

Duty Type:

Intermittent

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.119 cubic inches

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Criticality Code Justification:

Feat

Time Delay:

0.006 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

125.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Established reliability, failure rate 1.000 percent

NSN 5945-01-323-1163

Electromagnetic Relay - Page 2 of 2



Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
16 wire lead all functions
Specification Data:
81349-mil-r-39016/54 government specification
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No
Fiig:
A03300