NSN 5945-01-323-6743

Reed Relay - Page 1 of 2

Specification Data:

81349-mil-r-83516/1 government specification



View Online at https://aerobasegroup.com/nsn/5945-01-323-6743

Overall Length:
0.770 inches
Overall Height:
0.290 inches
Overall Width:
Between 0.290 inches and 0.310 inches
Fragility Factor:
Moderately rugged
End Application:
An/swg-3b
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
450.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.110 cubic inches
Nonpile-up Main Contact Arrangement:
1 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:
12.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
250.0 milliamperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
28.0 dc
Energizing Element Power Rating:
3.0 volts-amperes
Test Data Document:
81349-mil-r-83516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
7 pin all functions

NSN 5945-01-323-6743

Reed Relay - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300