

View Online at <https://aerobasegroup.com/nsn/5945-01-324-4212>

Overall Length:

Between 78.74 millimeters and 80.26 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Length:

66.421 millimeters single mounting facility and 66.929 millimeters single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

50.04 millimeters single mounting facility and 51.56 millimeters single mounting facility

Overall Height:

Between 88.90 millimeters and 91.94 millimeters

Overall Width:

Between 62.74 millimeters and 64.26 millimeters

Unthreaded Mounting Hole Diameter:

4.851 millimeters single mounting facility and 5.105 millimeters single mounting facility

End Application:

5805-01-188-3993 central office, telephone, automatic

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

208.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac

Terminal Type And Quantity:

6 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300