

View Online at <https://aerobasegroup.com/nsn/5945-01-324-4212>

**Overall Length:**

Between 78.74 millimeters and 80.26 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

66.421 millimeters single mounting facility and 66.929 millimeters single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

50.04 millimeters single mounting facility and 51.56 millimeters single mounting facility

**Overall Height:**

Between 88.90 millimeters and 91.94 millimeters

**Overall Width:**

Between 62.74 millimeters and 64.26 millimeters

**Unthreaded Mounting Hole Diameter:**

4.851 millimeters single mounting facility and 5.105 millimeters single mounting facility

**End Application:**

5805-01-188-3993 central office, telephone, automatic

**Frequency In Hertz:**

Between 50.0 and 60.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

1 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

208.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

500.0 milliamperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

120.0 ac

**Terminal Type And Quantity:**

6 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300