## NSN 5945-01-324-9545

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-324-9545
Overall Length:
0.810 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.062 inches single mounting facility and 1.078 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.395 inches single mounting facility and 0.415 inches single mounting facility
Overall Height:
0.810 inches
Overall Width:
0.640 inches
Mounting Slot Width:
0.131 inches single mounting facility and 0.151 inches single mounting facility
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
End Application:
F15e cbil
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
360.0 ohms single winding and 440.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.420 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary

Time Delay:

0.006 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius single winding

## NSN 5945-01-324-9545

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:** 

200.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

14 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300