## NSN 5945-01-324-9602

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-324-9602

**Thread Class:** 2a mounting facility bushing **Thread Direction:** Right-hand mounting facility bushing **Body Style:** Cylindrical frame Thread Length: 0.165 inches mounting facility bushing **Body Diameter:** Between 0.240 inches and 0.260 inches **Body Length:** Between 0.490 inches and 0.510 inches **Environmental Protection:** Dustproof and vibration resistant **Maximum Operating Temp:** 185.0 degrees fahrenheit **Fragility Factor:** Moderately rugged **Actuator Diameter:** 0.060 inches **End Application:** Walleye mk 64 **Inclosure Type:** Fully enclosed **Magnetic Coil Quantity:** 1 **Duty Type:** Intermittent **Terminal Location:** Circumference **Voltage Rating In Volts:** Between 25.0 dc and 35.0 dc **Mounting Facility Type And Quantity:** 1 threaded bushing **Current Rating:** 1.0 amperes **Storage Type:** General purpose warehouse **Cubic Measure:** 0.027 cubic inches

Thready Qty Per Inch (tpi): 80 power takeoff facility stud

## **NSN 5945-01-324-9602** Electrical Solenoid - Page 2 of 2



Actuator Stroke Type:
Pull
Linear Force Delivered:
3.0 grams
Power Takeoff Connection Type:
External threads
Thread Size:
0.138 inches mounting facility bushing
Thread Series Designator:
Unf power takeoff facility stud
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A134a0