# NSN 5945-01-325-0381

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-325-0381

## **Overall Length:**

1.025 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

## **Overall Height:**

1.010 inches

## **Overall Width:**

0.525 inches

#### Mounting Slot Width:

0.140 inches single mounting facility and 0.160 inches single mounting facility

## **Environmental Protection:**

Dustproof and hermetic

## **Fragility Factor:**

Moderately rugged

## **End Application:**

5805-01-188-3993 central office, tele

## Winding Quantity:

1

## Purpose For Which Designed:

General

## **Coil Quantity:**

1

## Winding Dc Resistance Rating:

288.0 ohms single winding and 352.0 ohms single winding

## **Duty Type:**

Continuous

## Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

## Storage Type:

General purpose warehouse

## **Features Provided:**

Polarized

#### **Cubic Measure:**

0.544 cubic inches

## **Mounting Facility Pattern:**

In-line single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

## Criticality Code Justification:

Feat

## Time Delay:

0.01 seconds fixed operate and release time

## NSN 5945-01-325-0381

Electromagnetic Relay - Page 2 of 2



## **Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

**Special Features:** 

Failure rate 0.1 percent

## **Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

8 pin all functions **Specification Data:** 81349-mil-r-6106/7 government specification **Shelf Life:** N/a **Unit Of Measure:** -- **Demilitarization:** No

Fiig:

A03300