## NSN 5945-01-325-0454

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-325-0454

## **Thread Class:** 2a mounting facility bushing **Thread Direction:** Right-hand mounting facility bushing **Body Style:** Cylindrical frame **Thread Length:** 0.200 inches power takeoff facility stud and 0.220 inches power takeoff facility stud **Body Diameter:** Between 0.480 inches and 0.520 inches **Body Length:** Between 1.490 inches and 1.510 inches **Environmental Protection:** Dustproof and vibration resistant Maximum Operating Temp: 185.0 degrees fahrenheit Actuator Length: Between 0.370 inches and 0.390 inches **Fragility Factor:** Moderately rugged Actuator Diameter: Between 0.100 inches and 0.120 inches **End Application:** Walleye mk 64 Inclosure Type: Fully enclosed Magnetic Coil Quantity: 1 **Duty Type:** Intermittent **Terminal Location:** End opposite actuator Voltage Rating In Volts: 19.0 dc Mounting Facility Type And Quantity: 1 threaded bushing **Current Rating:** 1.5 amperes Storage Type: General purpose warehouse **Cubic Measure:** 0.320 cubic inches

## NSN 5945-01-325-0454

Electrical Solenoid - Page 2 of 2



Thready Qty Per Inch (tpi): 80 power takeoff facility stud Actuator Stroke Type: Push Linear Force Delivered: 0.65 pounds Power Takeoff Connection Type: External threads Thread Size: 0.250 inches mounting facility bushing **Thread Series Designator:** Unf mounting facility bushing Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A134a0